


DWG NO.
C-101267

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.

LDC	-
DIST	-



TOP-LINK

Notes:

- △ Material(材质):
1) Body : C36000
2) Plating : C36000 or C27000
3) Sealing : Stainless steel wire
2) Plating(电镀):
1) Body: Min 0.1um Gold plating over min. 1.4um Nickel plating
2) Body: 镀金0.1um Min 镍底1.4um Min)
3) Plunger: Min 0.4um Gold plating over min. 1.4um Nickel plating
4) Plunger: 镀金0.4um Min 镍底1.4um Min)
3) Mechanical(机器性能):
1) Force(力):
2) Stroke to 4.05mm length and measure force: 90gf Min
(压缩到4.05mm的力: 90gf Min)
2) Total stroke(总行程) : 1.50mm
4) Durability(寿命): 10,000 cycle min.
3) Electrical(电性能)
1) Contact resistance(接触抵抗): 30mOhm Max.
2) Voltage rating(额定电压): 36V DC Max
3) Current rating(额定电流): 2.0A

DIMENSIONS IN MM				TOLERANCES UNLESS OTHER SPECIFIED			
0	= ± -			0.0	= ± 0.15		
0.00	= ± 0.10			0.000	= ±		
ANGLE: ±1°				SURF. TEXTURE: 32/			
REMOVE BURRS, BREAK SHARP EDGES R0.05 MAX				DO NOT SCALE PRINT			
NAME		PGGD PIN		SCALE		1:1	
PG-0.5-2.5-2.0-0.5-1.5-3.7-5.2		DWG NO.		A4		C-101267	
FIN		HT TR		REL		Top-Link Electronics	
PART NUMBER		101267-1		SHEET 1 OF 1		REV A	

USED ON

-