



DWG NO.
C-101287

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.

LDC
-
DIST
-



TOP-LINK



Notes:

Material:

1)Plunger & Body : CuZn36 Pb3, H02 (C36000)

or CuZn39 PB3 or CuZn38 PB2.

2)Spring : Stainless steel wire

2 Plating

1)Body: Min 0.1um Gold plating over min. 1.4um Nickel plating

2)Plunger: Min 0.4um Gold plating over min. 1.4um Nickel plating

3 Mechanical

1)Total stroke : 1.2mm

2)Durability: 10,000 cycle min.

4 Electrical

1)Contact resistance: 30mOhm Max.

2)Operating voltage: 36VDC

DIMENSIONS IN MM				TOLERANCES UNLESS OTHER SPECIFIED			
0	= ±	-		0.0	= ±0.15		
0.00	= ±	0.10		0.000	= ±		
ANGLE: ±1°							
SURF TEXTURE: 32/							
REMOVE BURRS, BREAK SHARP EDGES R0.05 MAX							
DO NOT SCALE PRINT							
MATL	1	HT TR	-	FIN	-	✓	
DWN	Jim	APVD	Lansing	Top-Link Electronics	Top-Link Electronics Ltd.		
CHK	Andy	REL					
NAME	POGGO PIN						
SCALE	1:1	A4	DWG NO.	C-101287	SHEET 1 OF 1	REV A	

USED ON

-

101287-1

PART NUMBER

Top-Link Electronics