


USED ON
-



Notes:
△Material(材质):

- 1)Body : C36000
- 2)Plunge : C36000
- 3)Spring : Stainless steel wire
- 2 Plating(电镀):
 - 1)Body: Min 0.1um Gold plating over min. 1.4um Nickel plating (Body: 镀金0.1um Min 镍底1.4um Min)
 - 2)Plunger: Min 0.25um Gold plating over min. 1.4um Nickel plating (Plunger: 镀金0.25um Min 镍底1.4um Min)
- 3 Mechanical(机械性能):
 - 1)Force: 90±20gf per pin at 2.5mm(力:2.5mm的力:90±20gf)
 - 2)Total stroke(总行程) : 3.40mm
 - 3)Durability(寿命): 10,000 cycle min.
- 4 Electrical(电性能)
 - 1)Contact resistance(接触抵抗): 30mOhm Max.
 - 2)Voltage rating(额定电压): 36V DC Max
 - 3)Current rating(额定电流): 3.0A

TOP-LINK

LDC	-
DIST	-

Update		2012/08/15
NEW		2008/05/19
REVISION RECORD	APVD	DATE
L TR		

DIMENSIONS IN MM			
TOLERANCES UNLESS OTHER SPECIFIED			
0	= ±		
0.0	= ±0.15		
0.00	= ±0.10		
0.000	= ±		
ANGLE: ±1°			
SURF TEXTURE: 32/			
REMOVE BURRS, BREAK SHARP EDGES R0.05 MAX			
DO NOT SCALE PRINT			
NAME		HT TR	FIN
PGGD PIN		-	-
PG-2.5-3.6-4.0-1.0-2.5-5.9-13.0			
SCALE		DWG NO.	
1:1		C-101416	
SHEET		REV	
1 OF 1		A1	

101416-1
PART NUMBER

A

B

C

D

4

3

2

1